

LINES HDR WIDE DYNAMIC DAY / NIGHT CAMERA (15CA453/ 15CA453C)

FEATURES

- Super Hi- Res. CCD with Star-Light 600TV lines (D/N)
- HDR Wide Dynamic Video Digital Signal Processor
- High Sensitivity, Low Smear, high S/N Ratio
- On Screen Display (OSD) set-up Menu
- Motion Detection, Privacy Marking, Mirror / Image function
- 2X Digital Zoom with Manual PAN / Tilt
- Challenging High Lighting Condition / adjustable Back Light Compensation
- S/N Ratio with Auto 3D-DNR / Auto IRIS Lens Cable Management
- IR Cut Removable / ICR External Control (15CA453C)
- Built in Video / Power Surge Protection.



IMAGE SYSTEM / ELECTRIC	15CA453	15CA453C
IMAGE SENSOR	1/3" CCD Image Sensor (Hi-Res)	
TOTAL PICK-UP	NTSC: 811x 507, PAL: 765 x 595	
EFFECTIVE PICTURE ELEMENTS	NTSC: 771 x 492, PAL: 753 x 582	
HORIZONTAL RESOLUTION	600 TV lines (D/N)	
MINIMUM ILLUMINATION	0.01 Lux	0.001 Lux
IR CUT	-	YES
ICR EXTERNAL CONTROL	-	YES, N.C. Type
DIGITAL ZOOM	2X · MANUAL PAN/TILT	
S/N RATIO WITH AOTO 3D-DNR	More than 56 dB	
GAMMA CHARACTERISTIC	0.45 /1.0	
AUTO / MANUAL ELECTRONIC SHUTTER	NTSC: 1/60s~1/120,000s, PAL: 1/50s~1/120,000s	
DIGITAL SOLW SHUTTER	2X~64X	
FLICKER LESS MODE	YES	
MIRROR FUNCTION	HORIZONTAL/VERTICAL	
IMAGE FUNCTION	FREEZE · NEGATIVE · CROSS LINE	
AUTO GAIN CONTROL	ON/OFF (6~24dB adjustable)	
WHITE BALANCE	Auto (ATW, AWB, FIXED, Manual) / 3200 ~ 10000 °K	
BACK LIGHT COMPENSATION	ON/OFF (48 Area Adjustable)	
MOTION DETECTION	YES	
VIDEO OUTPUT / AUDIO OUTPUT	Video: 1 Vp-p / 75 Ohms; Audio: 2Vp-p Max	
DAY & NIGHT	Auto (Level adjustable), Color, B/W	
PRIVACY MASKING	ON/OFF (4 Area adjustable)	
SYNCHRONOUS SYSTEM	EXT. /INT.SYNC./ (LINE LOCK OPTION)	
POWER SUPPLY / ENVIRONMENT/ MECHANISM		
POWER SUPPLY	AC24V / DC12V; 4W Power Consumption	
OPERATION TEMPERATURE	-10°C~65°C (14℉~149℉)	
DIMENSION	56(W) x 60(H) x 116.5(L) mm	

SOLE AGENT: