

DAY / NIGHT COLOUR CAMERA (SCB-231PRO)



FEATURES

- High resolution DSP camera
- Lumii technology
- 1/3" Sony Exview HAD CCD Sensor
- 540 TV lines day and night camera
- 0.01 Lux minimum illumination

SCB-231PRO - SPECIFICATIONS

IMAGE SYSTEM	
IMAGE SENSOR	1/3" Sony CCD
EFFECTIVE PIXELS	752 (H) x 582 (V)
IMAGING AREA	4.9mm x 3.7mm
ELECTRIC	
SYNC SYSTEM	Internal
HORIZONTAL RESOLUTION	540 TV Lines
SCANNING SYSTEM	2:1 interlace V: 50Hz, H: 15.625KHz
LENS MOUNT	CS
IRIS CONTROL	DC iris driver only
GAMMA CORRECTION	0.45
MINIMUM ILLUMINATION	0.2 lux(F1.2, 3200°K, AGC on, 50 IRE); 0.01 lux(F1.2, 3200°K, AGC on, 10 IRE)
S/N RATIO	50 dB (AGC off)
GAIN CONTROL	On / Off
ELECTRIC SHUTTER	1/50 - 1/100,000 sec.
BLC	Auto
WHITE BALANCE	Auto (2600°K - 9500°K)
FLICKERLESS	On/Off; Fix shutter speed: NTSC=1/100s, PAL=1/120
DAY/ NIGHT	Digital day/night on/off
VIDEO OUTPUT	1 Vpp composite output, 75 Ohm
POWER SUPPLY / ENVIRONMENT/ MECHANISM	
POWER SUPPLY	DC12V / AC85V-265V
POWER CONSUMPTION	3.5W (max)
OPERATION TEMPERATURE	-10°C - 50 °C
OPERATION HUMIDITY	90% RH
STORAGE TEMPERATURE	-20°C - 60 °C
DIMENSION (WXHXD)	50mm (W) x 56mm (H) x 115mm (D)
WEIGHT	~ 500g approx.

SOLE AGENT: