

VARIFOCAL COLOUR DOME CAMERA (MTC-2438DHQ)

FEATURES

- Super Hi-Res. Dome Camera
- 540 TV Lines
- 1/3" SONY Colour CCD
- 0.25 lux at F1.2
- 10 Bit Digital Signal Processing
- Built-in Aspherical Lens
- AES/AGC/BLC/FL Switchable(ON/OFF)



MTC-2438DHQ - SPECIFICATIONS

IMAGE SYSTEM	
IMAGE SENSOR	1/3" SONY Color CCD
EFFECTIVE PIXELS	795(H) X 596(V)
ELECTRIC	
SYNC SYSTEM	Internal
HORIZONTAL RESOLUTION	540 TV Lines
MINIMUM ILLUMINATION	0.25Lux@F1.2
S/N RATIO	More Than 50dB (AGC Off)
BLC	ON/OFF (Switchable)
AUTOMATIC GAIN CONTROL	ON/OFF (Switchable)
F.L. (FLICKERLESS)	ON/OFF (Switchable)
AES	ON/OFF (Switchable)
DC LEVEL	The VR for adjusting the IRIS level of auto Iris lens.
WHITE BALANCE	AWB
VIDEO OUTPUT	1Vp-p Composite / 75Ω
LENS/ANGLE OF VIEW(H)	f2.9mm~10.0mm/F1.3 Aspherical Auto Iris Lens / 108.2 ~47.6 degrees
POWER SUPPLY / ENVIRONMENT/ MECHANISM	
POWER SUPPLY	Standard:12Vdc; 2.0W (Option:12Vdc/24Vac)
OPERATION TEMPERATURE	-10°C to 50°C
STORAGE TEMPERATURE	-20°C to 60°C
OPERATION HUMIDITY	85% r.h or less
DIMENSION (WXHXD)	118(DIA) X 88(H)mm
WEIGHT	12Vdc: 300g; 12Vdc/24Vac: 370g

SOLE AGENT: