

H.264 NETWORK DIGITAL VIDEO RECORDER (SLIM TYPE) (VP-HL410V)



FEATURES

- Advanced H.264 compression technology
- Advanced CMS included
- Pentaplex operation: Live, record, playback, remote record, remote setting, remote playback
- Max frame rate per system: 400fps live display, 200fps recording, 100fps playback
- Intelligent 3G/GPRS support for mobile phone / PDA remote surveillance
- 1 internal SATA harddisk support; external e-SATA harddisk support (optional)
- Integrated driver for USB type touch screen display (optional)
- Long time recording max. approx 1000 hours recording
- Remote live / playback / backup / DVR configuration support
- DVR control by USB mouse / IR remote controller / touch panel display (optional)
- Audio support: 1 in 1 out
- Independent camera configuration for each channel
- Multi-language support
- RS-485 interface for PTZ camera control
- Email alert and FTP upload for alarm notification
- PIP display and channel screen popup when motion/ sensor triggered
- Multiple network connections at the same time
- Time/ event/ calendar search for quick playback retrieval
- User-friendly interface for easy operation

SOLE AGENT:

VP-HL410V SPECIFICATIONS

VIDEO	
COMPRESSION	H.264
VIDEO INPUT	4 channels (BNC)
VIDEO OUTPUT	BNC x 2 (TV out x 1, SPOT x 1), VGA out x 1
AUDIO	
INPUT/ OUTPUT	Input: RCA x 1 ; output: RCA x 1
DISPLAY	
DISPLAY FRAME RATE	100 fps
RESOLUTION	720 x 576 (PAL)
SPLIT SCREEN	1 / 4 / SEQ
MODE	Zoom x 2 / PIP / Auto SEQ
ON-SCREEN DISPLAY (OSD)	Graphic User Interface
RECORDING	
RESOLUTION	720 x 576 , 720 x 288, 360 x 288 (PAL)
VIDEO QUALITY	5 levels: highest , high , normal , low , lowest
MODE	Normal / motion / alarm / schedule
FRAME RATE	25fps (720 x 576) , 50fps (704 x 288) , 100fps (352 x 288)
PRE-ALARM RECORDING	16MB (approximately 8-10secs)
PLAYBACK	
DISPLAY	1, 4
FRAME RATE	25fps (720 x 576) , 50fps (704 x 288) , 100fps (352 x 288)
SEARCH	Time / event / calendar
SPEED	Normal, pause, REW & FF (2, 4, 8, 16, 32, 64x)
STORAGE	
DEVICE (SATA)	Supports 1 internal harddisk, external e-SATA interface
BACKUP	
MEDIA	USB 2.0, remote network backup
PAN/ TILT / ZOOM (PTZ)	
SIGNAL INPUT	RS-485 Interface
PHYSICAL	
CONTROL DEVICE	Remote control, USB mouse/ USB touch panel (optional)
DIMENSION	285(W) x 48(H) x 224(D) mm
WEIGHT	Approx 3 KG
POWER	External adaptor, AC100-240V/In, DC12V (3A) above

SOLE AGENT: